

Charging S

PV & ESS & EV Charging Solution

-
-
-

-
-

SHENZHEN MEGMEET ELECTRICAL CO., LTD.

FOLLOW US





Contents

01-14	Charger
15-28	Charging Module
29-31	Charger Components
32	R&D Capability
33-34	Manufacturing Capacity

Super Fast Charging Stations

SFC 30



Universal compatibility



Smart connectivity



Safe & reliable



Efficient & convenient

AC Input	
	≥
DC Output	
	≥
	≥
	≥
	≥
Working Environment Conditions	
	≥
Function	
Appearance	

Super Fast Charging Stations

SFC 40



AC Input

> >

DC Output

≡ ≡ > ≡

Working Environment Conditions

≡

Function

Appearance

Super Fast Charging Stations


SFC 60



AC Input	
	≥
DC Output	
	≥
	≥
	≥
	<
Working Environment Conditions	
	≥
Function	
Appearance	

Super Fast Charging Stations

SFC 60 to 180



Fast charging



Safe & efficient



Intelligent operation & Maintenance



Flexible expansion

AC Input	
	> >
DC Output	
	≡
	≡
	≡
	≡
Working Environment Conditions	
	≡
Function	
Appearance	

Super Fast Charging Stations

SFC 150



Fast charging



Safe & efficient



High-grade protection



Flexible efficient

AC Input

≡

DC Output

≡

≡

≡

≡

Working Environment Conditions

≡

Function

Appearance



AC Input	
	≥
DC Output	
	≈
	≈
	≥
	≈
Working Environment Conditions	
	≈
Function	
Appearance	

Split Type Super Fast Charging Stations



- 

Liquid cooling supercharging
- 

Intelligent operation & maintenance

- 

Flexible allocation
- 

Safe & efficient

AC Input				
DC Output				
Working Environment Conditions				
Function				
Appearance				

20 kW Charging Module



Wide constant power range




State grid unified size



Flexible expansion



Intelligent control



AC Input

<

>

>

<

DC Output

≡

≡

≡

≡

≡

Monitor

Working Environment Conditions

≡

>

Product Reliability and Safety

Alarm and Protection

Dimensions and Weight

20 kW Charging Module



Low voltage and high current




High power density



Flexible expansion



Intelligent control



AC Input	
	<
	> >
	<
DC Output	
	≡
	≡
	≡
	≡
Monitor	
Working Environment Conditions	
	≡ >
Product Reliability and Safety	
	>
Alarm and Protection	
Dimensions and Weight	

20 kW Charging Module



Low voltage and high current




High power density



Flexible expansion



Intelligent control



AC Input

<

>
<

DC Output

≡

≡

≡

≡

≡

Monitor

Working Environment Conditions

≡ >


Product Reliability and Safety

>

Alarm and Protection

Dimensions and Weight





>

Alarm and Protection


Dimensions and Weight

25 kW Charging Module




DC Input	
	<
DC Output	
	>
Monitor	
Working Environment Conditions	
Product Reliability and Safety	
Alarm and Protection	
Dimensions and Weight	

Charger Communication Control Unit (CCU)




Input voltage: —
Interface parameters: — — — —

Charger Telematics Control Unit (TCU)




Input voltage: —
Storage chip: — —
Interface parameters: — — —

Charger Protocol Converter (PLC)



R&D CAPABILITY



- -
 -
 -
 -
 -
- -
 -
 -
 -
 -

Charging standards:	—	Communication port:	—
Electricity supply:	—	Dimension:	—
	—		
Working power consumption:	— <	Range of working temperature:	—





ODM

OEM

